

ProKOTE SS
PROTECTION FORMULA
SMOKE-STOP

SMOKE REDUCING TREATMENT • FOR HIGH-MILEAGE ENGINES

- Multiple-action formula that reduces oil burning, exhaust smoke, emissions and pollution.
- Extends engine life in aged or abused engines.
- Designed to reduce further engine friction and wear.
- Increases oil viscosity.
- Improves compression and power.
- Reduces temperature and noise levels.
- Maintains dry and older gasket pliability restoring sealing properties.
- Contributes to seal oil leaks.
- Helps decrease oil and fuel consumption.
- Reduces sluggish performance and repair frequency.
- Specially formulated with the unique proprietary **ProKote AF** (Anti-Friction) anti-wear and extreme pressure EP agents.
- Compatible with all brands of oil including synthetics.
- Contains no solids.

DIRECTIONS: ENGINE OIL RESERVOIR (capacity up to 5 quarts -or- liters-): Add the content of this bottle (8 ounces). For larger engines add two bottles.

Note: Repeat every 3,000 to 5,000 miles (or 5,000 to 8,000 kilometers).

USES: For all types of gas, diesel, alcohol and propane powered vehicles, both 4-cycle and 2-cycle engines, marine engines, etc.

CAUTION: Contains synthetic hydrocarbon derivatives. If swallowed, call a physician immediately. Do not induce vomiting. Keep out of reach of children.

PROKOTE INTERNATIONAL, Inc.
E-mail: info@prokote.com
www.prokote.com

Genesee Technology
Made in U.S.A.

MEMBER OF



PROKOTE SS
SMOKE-STOP

#1 WORLD WIDE

ProKOTE SS
ENGINE • SMOKE REDUCER
SMOKE-STOP

REDUCE:

SMOKE
EMISSIONS
OIL LEAKS
POLLUTION
REPAIR FREQUENCY
SLUGGISH PERFORMANCE



ProKOTE ...
MUCH MORE
PROTECTION!

8 FL OZ
236 ml